

ZX7-2TT/200S 逆变直流手工弧焊机 Inverter DC ARC welding machine

安装示意图 Installation diagram



产品特点 Features

- ◆ 有效防水、除静电、耐腐蚀、体积小、重量轻、抗干扰、良好电流调节功能。
- ◆ 焊接品质好，熔池深。
- ◆ 过压过流自动保护。
- ◆ 可连续工作，性能稳定，具有电压波动自动补偿能力。
- ◆ 十分适合装修，五金等行业。
- ◆ Efficient waterproof, antistatic, anticorrosion, small in size, light in weight, anti-interference, excellent current adjustment function.
- ◆ Good welding quality, deep welding pool.
- ◆ Auto protection of over current, over voltage.
- ◆ Can continuous work, stable performance, automatic compensation for voltage fluctuation.
- ◆ Suitable for decoration and hardware industry etc.



ZX7-200TT

技术参数 Technical Parameters ZX7-2TT ZX7-200S

输入电源电压频率(V,Hz) Input power Voltage Frequency(V, Hz)	AC220(single phase)±15%,50/60	
额定输入电源容量(KVA) Rated input power capacity(KVA)	4.5	4.5
空载电压(V) No-load voltage(v)	56	56
输出电流调节范围(A) Output current range.(A)	20-200	20-200
额定输出电压(V) Rated output voltage(V)	25.6	25.6
负载持续率(%) (25°C) Duty cycle (%)	60	60
空载损耗(W) No-load loss(w)	40	40
效率(%) Efficiency(%)	85	85
功率因数(COSφ) Power factor (COSφ)	0.93	0.93
绝缘等级 Insulation class	F	F
重量(KG) Weight(KG)	5	5.5
外形尺寸(mm) Overall dimension(mm)	290×130×203	290×130×203
外壳保护等级 Case protection degree	ip21S	ip21S
适合焊条直径(mm) Suitable diameter of rod(mm)	1.6-2.5	1.6-3.2



ZX7-200S